Car Seat Adaptor for Elite/Classic/Summit Double Stroller

HIGH PERFORMANCE STROLLERS

Adaptor Bracket



Spring Support Bar

This Kit Includes:

2 Adaptor Brackets
1 T-Shaped Support Bar
1 U-Shaped Support Bar
1 Straight Support Bar
1 Spring Support Bar

Compatible Car Seat & Usage Guide

Baby Trend Expedition: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Baby Trend Gabriella Infant Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Baby Trend Stride Sport Travel System Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Baby Trend StrideZ: Uses the 2 Adaptor Brackets, U-Shaped Support Bar (facing up)

Britax Companion: Uses the 2 Adapter Brackets, the U-Shaped Support Bar (facing up), and the T-Shaped Support Bar

Britax Romer: Uses the 2 Adapter Brackets, the U-Shaped Support Bar (facing up), and the T-Shaped Support Bar

Cosco Sprint Travel System: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Eddie Bauer Adventurer: Uses the 2 Adapter Brackets, the U-Shaped Support bar (facing up) and the Spring Support Bar

Evenflo Aura Elite: Uses the 2 Adapter Brackets and the U-Shaped Support bar (facing up)

Evenflo Embrace 5: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Evenflo Embrace LX Infant Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Evenflo Journey Premier Travel System Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Evenflo Nestino Odyssey Travel System Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Graco Infant SafeSeat Step 1: Uses the 2 Adaptor Brackets and the U-Shaped Support Bar (facing up)

Graco SnugRide & SnugRide 2: Uses the 2 Adaptor Brackets and U-Shape Support Bar (facing up)

Maxi Cosi Cabrio: Uses the 2 Adaptor Brackets ONLY

Maxi Cosi Mico: Uses the 2 Adaptor Brackets ONLY

Peg Perego Primo Viaggio SIP: Uses the 2 Adaptor Brackets, U-Shaped Support Bar (facing down), the Spring Support Bar, and the Straight Support Bar

Peg Perego Primo Viaggio SIP 30/30: Uses the 2 Adaptor Brackets, U-Shaped Support Bar (facing down), the Spring Support Bar, and the Straight Support Bar

Safety 1st Designer 22: Uses the 2 Adaptor Brackets, U-Shaped Support Bar (facing up) and the Spring Support Bar

The 2009 City Series Car Seat Adaptor for Double Stroller is designed to be used with only your City Mini, City Series, City Classic, City Elite or Summit 360 double stroller. This car seat adaptor is only compatible with these stroller models.

Before you start, please refer to the usage guide located in the bottom left corner to determine which adaptor pieces your car seat requires.

1 Un-Velcro seat from footplate area so that silver metal frame bars are visible.

2 Unsnap all snaps on seat below folding mechanism of double stroller.

3 Loosen adjustment knobs on double car seat adaptor.

4 Slide adaptor unit onto right side of the stroller frame.

5 Apply center clamp over center metal frame bar.

6 Tighten both adjustment knobs until center clamp is secure onto stroller frame.

7 On the right side of the stroller frame, attach single clamp between the lowest rivet and the lowest snap on the stroller frame.

8 Tighten adjustment knob until clamp is secure onto stroller frame.

9 Pull seat fabric down to re-attach to stroller frame using Velcro on and underneath footplate. To do this, thread the Velcro strap between the frame and the adaptor bar. Re-attach snap on right side of stroller frame above single clamp.

10a If your car seat adaptor requires the Straight Support Bar, insert the bar on right adaptor bracket underneath red compression lock by pressing black ribbed button.

10b Slide the Straight Support Bar into left adaptor bracket hole to secure in place.

11 Open the compression locks on the Car Seat Adaptor Brackets by flipping the red latches up.

12 Insert the U-Shaped Support Bar with the curved end pointing up or down, depending on what your car seat requires. (See usage guide)

13 If your car seat requires the Spring Support Bar, insert the Spring Support Bar into the front of the U-Shaped Bar by squeezing it into the open holes.

14 Place your car seat onto the U-Shaped Bar, making sure that the Spring and Support Bars engage the locking mechanisms if/where applicable. Adjust the U-Shaped Support Bar to proper length by sliding the U-Shaped Bar in and out, using the car seat to ensure proper distance. The adaptor brackets should line up with the handle hinge of the car seat.

15 Close compression locks by flipping the red latches down.



figure A

16 If applicable, place the T-Shaped Bar onto the car seat and tighten strap using D-Ring and Velcro. (figure A)

17 Secure your car seat onto the stroller using the safety belt on the Car Seat Adapter Brackets.

How to use your car seat adaptor safely

NOTE: If only the car seat is in use without second child, the car seat adaptor must be locked in the center of the stroller.

1 To use with 1 child in left stroller seat and 1 child in the car seat, make sure adaptor brackets are locked into place on right side. Press red compression lock down to secure adaptor into place.

2 To use with 1 child in car seat, release red compression lock. Slide adaptor bar to the center. Press red compression lock to secure adaptor into place.

8575 Magellan Parkway, Suite 1000 • Richmond, VA 23227 • T: 800-241-1848 • F: 804-262-6277 • www.babyjogger.com

Car Seat Adaptor for Mini Double Stroller

HIGH PERFORMANCE STROLLERS

The 2009 City Series Car Seat Adaptor for Double Stroller is designed to be used with only your City Mini, City Series, City Classic, City Elite or Summit 360 double stroller. This car seat adaptor is only compatible with these stroller models.

Before you start, please refer to the usage guide located in the bottom left corner to determine which adaptor pieces your car seat requires.

Adaptor Bracket



Straight Support Bar

Spring Support Bar

This Kit Includes:

2 Adaptor Brackets
1 T-Shaped Support Bar
1 U-Shaped Support Bar
1 Straight Support Bar
1 Spring Support Bar

Compatible Car Seat & Usage Guide

Baby Trend Expedition: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Baby Trend Gabriella Infant Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Baby Trend Stride Sport Travel System Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Baby Trend StrideZ: Uses the 2 Adaptor Brackets, U-Shaped Support Bar (facing up)

Britax Companion: Uses the 2 Adapter Brackets, the U-Shaped Support Bar (facing up), and the T-Shaped Support Bar

Britax Romer: Uses the 2 Adapter Brackets, the U-Shaped Support Bar (facing up), and the T-Shaped Support Bar

Cosco Sprint Travel System: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Eddie Bauer Adventurer: Uses the 2 Adapter Brackets, the U-Shaped Support bar (facing up) and the Spring Support Bar

Evenflo Aura Elite: Uses the 2 Adapter Brackets and the U-Shaped Support bar (facing up)

Evenflo Embrace 5: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Evenflo Embrace LX Infant Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Evenflo Journey Premier Travel System Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Evenflo Nestino Odyssey Travel System Car Seat: Uses the 2 Adaptor Brackets and U-Shaped Support Bar (facing up)

Graco Infant SafeSeat Step 1: Uses the 2 Adaptor Brackets and the U-Shaped Support Bar (facing up)

Graco SnugRide & SnugRide 2: Uses the 2 Adaptor Brackets and U-Shape Support Bar (facing up)

Maxi Cosi Cabrio: Uses the 2 Adaptor Brackets ONLY

Maxi Cosi Mico: Uses the 2 Adaptor Brackets ONLY

Peg Perego Primo Viaggio SIP: Uses the 2 Adaptor Brackets, U-Shaped Support Bar (facing down), the Spring Support Bar, and the Straight Support Bar

Peg Perego Primo Viaggio SIP 30/30: Uses the 2 Adaptor Brackets, U-Shaped Support Bar (facing down), the Spring Support Bar, and the Straight Support Bar

Safety 1st Designer 22: Uses the 2 Adaptor Brackets, U-Shaped Support Bar (facing up) and the Spring Support Bar

1 Un-Velcro both black straps underneath seat.
2 Unsnap all seat snaps below the Baby Jogger logo on left and right sides of stroller.
3 Loosen adjustment knobs on double car seat adaptor.
4 Slide adaptor unit onto right side of the stroller frame.
5 Apply center clamp over center metal frame bar.
6 Tighten both adjustment knobs until center clamp is secure onto stroller frame.

7 On the right side of the stroller frame, tighten the right clamp so it is positioned below the 2 rivets and in between the 2 snaps on the frame.
8 Pull seat fabric down and re-attach by snapping snaps and Velcroing the 2 black straps underneath the seat.

9a If your car seat adaptor requires the Straight Support Bar, insert the bar on right adaptor bracket underneath red compression lock by pressing black ribbed button.
9b Slide the Straight Support Bar into left adaptor bracket hole to secure in place.
10 Open the compression locks on the Car Seat Adaptor Brackets by flipping the red latches up.

11 Insert the U-Shaped Support Bar with the curved end pointing up or down, depending on what your car seat requires. (See usage guide)
12 If your car seat requires the Spring Support Bar, insert the Spring Support Bar into the front of the U-Shaped Bar by squeezing it into the open holes.
13 Place your car seat onto the U-Shaped Bar, making sure that the Spring and Support Bars engage the locking mechanisms if/where applicable. Adjust the U-Shaped Support Bar to proper length by sliding the U-Shaped Bar in and out, using the car seat to ensure proper distance. The adaptor brackets should line up with the handle hinge of the car seat.



figure A

14 Close compression locks by flipping the red latches down.
15 If applicable, place the T-Shaped Bar onto the car seat and tighten strap using D-Ring and Velcro. (figure A)
16 Secure your car seat onto the stroller using the safety belt on the Car Seat Adapter Brackets.

How to use your car seat adaptor safely

NOTE: If only the car seat is in use without second child, the car seat adaptor must be locked in the center of the stroller.

1 To use with 1 child in left stroller seat and 1 child in the car seat, make sure adaptor brackets are locked into place on right side. Press red compression lock down to secure adaptor into place.

2 To use with 1 child in car seat, release red compression lock. Slide adaptor bar to the center. Press red compression lock to secure adaptor into place.

8575 Magellan Parkway, Suite 1000 • Richmond, VA 23227 • T: 800-241-1848 • F: 804-262-6277 • www.babyjogger.com